



Comes with:



- + 1 vice
- + 1 chuck
- + 1 cone puller

PPE22VE
Bench drill with 22 mm capacity –
230 V – variable speed control
Reference: PPM00400003
EAN: 3221912396914

Motor power kW: 1.2
Weight: 87 kg
Height: 380 mm
Minimum spindle speed: 150 rpm
Maximum drilling capacity: 22 mm
Column diameter: 80 mm
D: distance between spindle and column (mm): 180
F: distance between spindle and table: 145 - 425 mm
Lighting: yes
Coolant: no
Soft descent: no

Cross table: no
V power supply: 230
Length: 635 mm
Width: 1085 mm
Maximum spindle speed: 5000 rpm
Morse taper: MT2
Spindle stroke: 90 mm
E: distance between spindle and base (mm): 650
Table dimensions: 470 x 280 mm
Interlocked screen: yes
Automatic descent: no
Semi-automatic tapping: no

Summary:

Dry drilling of metals, plastics, wood, intensive use 6 to 7 hours/day. Capacity 22 mm, stroke 90 mm, variable speed 150 to 5000 rpm, 1200 W motor, 230 V single-phase. Equipment: Speed variator, high-speed drilling, feed table. Supplied with a box of 25 TSP TIVOLY Premium coated drill bits, Ø1 to 13 mm in ½ increments.